

## CLAIMS

What is claimed is:

1. A method implemented in a processor system for a sender to encrypt an  
5 electronic message prior to sending to a receiver, comprising the steps of:  
generating an ad hoc public key and private key asymmetric key pair that is  
uniquely associated with both the sender and the receiver;  
encrypting the private key, the encrypted private key known only to the  
sender;  
10 creating an index value that is uniquely associated with the key pair, the  
index value utilized for key retrieval;  
storing in a key server at least the encrypted private key together with the  
associated index value; and  
encrypting the electronic message by utilizing the public key.  
15
2. The method of claim 1 wherein the private key is encrypted symmetrically by  
utilizing a sender secret.
3. The method of claim 1 wherein the index value is known only to the sender.  
20
4. The method of claim 3 wherein the creating step comprises the steps of:  
obtaining an identity value by utilizing at least a unique identification for the  
sender and a unique identification for the receiver; and  
25 computing from the identity value an index value by utilizing a sender  
secret, the index value uniquely associated with the key pair, the index value  
utilized for key retrieval and known only to the sender.
5. The method of claim 1 wherein the electronic message is an electronic mail  
message.

6. The method of claim 1 wherein the key pair is a set of at least one key pair, each key pair associated with a validity field.
- 5 7. The method of claim 1 wherein the ad hoc public key and private key asymmetric key pair is an ad hoc symmetric key.
8. A method implemented in a processor system for a receiver to decrypt an encrypted electronic message received from a sender, comprising the steps of:  
10 authenticating the receiver to the sender;  
deriving an index value that is uniquely associated with an ad hoc public key and private key asymmetric key pair, the key pair uniquely associated with both the sender and the receiver;  
retrieving an encrypted private key from a key server by utilizing the index  
15 value, the encrypted private key known only to the sender; and  
decrypting the encrypted electronic message by utilizing the encrypted private key.
9. The method of claim 8 wherein the decrypting step comprises the steps of:  
20 obtaining an unencrypted private key from the encrypted private key by utilizing a sender secret; and  
decrypting the encrypted electronic message by utilizing the unencrypted private key.
- 25 10. The method of claim 8 wherein the index value is known only to the sender.
11. The method of claim 10 wherein the deriving step comprises the steps of:  
obtaining an identity value by utilizing at least a unique identification for the sender and a unique identification for the receiver; and

computing from the identity value an index value by utilizing a sender secret, the index value uniquely associated with an ad hoc public key and private key asymmetric key pair, the key pair uniquely associated with both the sender and the receiver, and the index value known only to the sender.

12. The method of claim 8 wherein the electronic message is an electronic mail message.

13. The method of claim 8 wherein the key pair is a set of at least one key pair, each key pair associated with a validity field, and the encrypted private key is selected from the set based on the validity field associated with the encrypted private key.

14. The method of claim 8 wherein the ad hoc public key and private key asymmetric key pair is an ad hoc symmetric key.

15. A processor system for a sender to encrypt an electronic message prior to sending to a receiver, comprising:

means for generating an ad hoc public key and private key asymmetric key pair that is uniquely associated with both the sender and the receiver;

means for encrypting the private key, the encrypted private key known only to the sender;

means for creating an index value that is uniquely associated with the key pair, the index value utilized for key retrieval;

means for storing in a key server at least the encrypted private key together with the associated index value; and

means for encrypting the electronic message by utilizing the public key.

16. The system of claim 15 wherein the key pair is a set of at least one key pair,  
each key pair associated with a validity field.
17. The system of claim 15 wherein the ad hoc public key and private key  
5 asymmetric key pair is an ad hoc symmetric key.
18. A processor system for a receiver to decrypt an encrypted electronic message  
received from a sender, comprising:
  - means for authenticating the receiver to the sender;
  - 10 means for deriving an index value that is uniquely associated with an ad hoc  
public key and private key asymmetric key pair, the key pair uniquely associated  
with both the sender and the receiver;
  - means for retrieving an encrypted private key from a key server by utilizing  
the index value, the encrypted private key known only to the sender; and
  - 15 means for decrypting the encrypted electronic message by utilizing the  
encrypted private key.
19. The system of claim 18, wherein the key pair is a set of at least one key pair,  
each key pair associated with a validity field, and the encrypted private key is  
20 selected from the set based on the validity field associated with the encrypted  
private key.
20. The system of claim 18 wherein the ad hoc public key and private key  
asymmetric key pair is an ad hoc symmetric key.